

IVM 40/12-1 H Z22

Mobile middle class industrial vacuum cleaner with EC turbine. Suitable for the safe vacuuming of fine and coarse solids in dust class H and for use in ATEX zone 22.



Order no. 9.990-266.0

- Suitable for use in ATEX zone 22
- Machine certified to dust class H

Technical data

EAN code		4066529007315
Supply voltage	V / Hz	220 - 240 / 50 - 60
Air flow	l/s / m³/h	43.8 / 158
Vacuum	mbar / kPa	249 / 24.9
Container content	l	40
Container material		Stainless steel
Rated input power	kW	1.2
Vacuuming type		Electric
Connection nominal diameter		ID 70
Accessory nominal diameter		ID 50 / ID 40
Sound pressure level	dB(A)	73
Main filter dust class		M
Filter area for main filter	m²	1.6
Secondary filter dust class		H
Filter area for secondary filter	m²	1.6
Weight without accessories	kg	51
Weight incl. packaging	kg	51
Dimensions (L × W × H)	mm	645 × 655 × 1140

Equipment

Main filter	Star filter
Secondary filter	Cartridge filter
Accessories included in the scope of delivery	no
Container emptying	Set-down trolley

■ included in the scope of supply.

Users must receive training on this device.



Certified for ATEX Zone 22

- Explosion-proof industrial vacuum for safe vacuuming in ATEX Zone 22.



Dust class H

- Overall device certified according to DIN EN 60335-2-69 for dust class H.
- For safely picking up solids and dusts up to dust class H.



Low-wear EC turbine

- Brushless design for low-wear operation.
- Suitable for three-shift operation thanks to a minimum service life of 5000 hours.

ACCESSORIES FOR IVM 40/12-1 H Z22

9.990-266.0



		Order no.	Description	
FILTERS				
Bag/star filter				
Star filter PE/PTFE el. M 1,6m²	1	9.990-222.0		■
Cartridge filter				
Cartridge filter PE H14 1,6m²	2	9.993-005.0		■
FILTER T/ NT				
Safety filter sets/bags				
Safety filter bag, 5 Piece(s), NT 75/1	3	6.904-420.0	For dust-free/low-dust emptying in conjunction with the 4.070-930.0 container, with dust disposal bag, electrically conductive. Checked and approved for dust class H.	☐
ACCESSORY SETS				
Accessory kit for solids/dust				
Oven cleaning accessory kit DN 50	4	9.989-938.0	Accessory kit for oven cleaning: ME hose 3 m (9.989-979.0), handle (9.989-899.0), suction tube (9.989-929.0), floor nozzle (9.989-935.0), reducer (9.989-712.0), adapter (9.993-011.0).	☐
Oven cleaning accessory kit DN 40	5	9.989-939.0	Accessory kit for oven cleaning: ME hose 3 m (9.989-976.0), handle (9.989-898.0), suction tube (9.989-928.0), floor nozzle (9.989-934.0), reducer (9.989-713.0), adapter (9.993-012.0).	☐
Food accessory kit DN 40	6	9.989-940.0	Food accessory kit DN 40: PU hose 3 m (9.989-970.0), handle (9.989-898.0), standard nozzle (9.989-838.0), brush (9.989-879.0), reducer (9.989-713.0), adapter (9.993-012.0).	☐
Food accessory kit DN 50	7	9.989-941.0	Food accessory kit: PU hose 3 m (9.989-973.0), handle (9.989-899.0), standard nozzle (9.989-844.0), brush (9.989-880.0), reducer (9.989-712.0), adapter (9.993-011.0).	☐
Accessory kit for overhead cleaning DN 40	8	9.989-942.0	Accessory kit DN 40 for overhead cleaning: suction tubes (9.989-920.0/9.993-008.0), handles (9.989-916.0/9.989-918.0), standard nozzle (9.989-838.0), brush (9.989-879.0), adapter (9.993-012.0).	☐
Accessory kit for overhead cleaning DN 50	9	9.989-943.0	Accessory kit DN 50 for overhead cleaning: suction tubes (9.989-921.0/9.993-009.0), handles (9.989-917.0/9.989-919.0), standard nozzle (9.989-844.0), brush (9.989-880.0), adapter (9.993-011.0).	☐
Accessory kit for solids/dust DN 40	10	9.989-659.0	Accessory kit DN 40 for industrial vacuum cleaners (solids and dust): EVA hose (9.988-088.0), handle (9.977-679.0), standard nozzle (9.988-401.0), reducer (9.989-690.0).	☐
Accessory kit for solids/dust DN 50	11	9.989-662.0	Accessory kit DN 50 for industrial vacuum cleaners (solids and dust): EVA hose (9.988-090.0), handle (9.977-678.0), standard nozzle (9.988-402.0), reducer (9.977-772.0).	☐
NOZZLES				
Standard nozzles				
Standard nozzle silicone FDA blue DN-F40	12	9.989-835.0		☐
Standard nozzle silicone FDA green DN-F40	13	9.989-836.0		☐
Standard nozzle silicone FDA red DN-F40	14	9.989-837.0		☐

■ Included in the scope of supply. ☐ Available accessories.

ACCESSORIES FOR IVM 40/12-1 H Z22
9.990-266.0



		Order no.	Description	
NOZZLES				
Standard nozzles				
Standard nozzle silicone FDA transparent DN-F40	15	9.989-838.0		☐
Standard nozzle silicone FDA white DN-F40	16	9.989-839.0		☐
Standard nozzle silicone FDA yellow DN-F40	17	9.989-840.0		☐
Standard nozzle silicone FDA blue DN-F50	18	9.989-841.0		☐
Standard nozzle silicone FDA green DN-F50	19	9.989-842.0		☐
Standard nozzle silicone FDA red DN-F50	20	9.989-843.0		☐
Standard nozzle silicone FDA transparent DN-F50	21	9.989-844.0		☐
Standard nozzle silicone FDA white DN-F50	22	9.989-845.0		☐
Standard nozzle silicone FDA yellow DN-F50	23	9.989-846.0		☐
Standard nozzle silicone DN40	24	9.988-401.0	Stretchy standard nozzle made from silicone, inner cone DN 40.	☐
Standard nozzle silicone DN50	25	9.988-402.0		☐
Standard nozzle cuttable rubber DN40	26	9.989-677.0	Standard nozzle, electroconductive, made from cuttable rubber. DN 40.	☐
Standard nozzle cuttable rubber DN50	27	9.989-675.0	Standard nozzle, electroconductive, made from cuttable rubber. DN 50.	☐
Floor nozzles				
Floor nozzle stainless steel AISI 304 DN-F40 blue	28	9.989-861.0		☐

■ Included in the scope of supply. □ Available accessories.

ACCESSORIES FOR IVM 40/12-1 H Z22
9.990-266.0



		Order no.	Description	
NOZZLES				
Floor nozzles				
Floor nozzle stainless steel AISI 316L DN-F50 blue	29	9.989-862.0		☐
Floor nozzle stainless steel AISI 316L DN-F40 green	30	9.989-863.0		☐
Floor nozzle stainless steel AISI 316L DN-F50 green	31	9.989-864.0		☐
Floor nozzle stainless steel AISI 316L DN-F40 red	32	9.989-865.0		☐
Floor nozzle stainless steel AISI 316L DN-F50 red	33	9.989-866.0		☐
Floor nozzle stainless steel AISI 316L DN-F40 transparent	34	9.989-867.0		☐
Floor nozzle stainless steel AISI 316L DN-F50 transparent	35	9.989-868.0		☐
Floor nozzle stainless steel AISI 316L DN-F40 white	36	9.989-869.0		☐
Floor nozzle stainless steel AISI 316L DN-F50 white	37	9.989-870.0		☐
Floor nozzle stainless steel AISI 316L DN-F40 yellow	38	9.989-871.0		☐
Floor nozzle stainless steel AISI 316L DN-F50 yellow	39	9.989-872.0		☐
Floor nozzle stainless steel AISI 316L DN-F40	40	9.989-914.0		☐
Floor nozzle stainless steel AISI 316L DN-F50	41	9.989-915.0		☐
Floor nozzle stainless steel 400 mm DN-F40	42	9.989-934.0		☐

■ Included in the scope of supply. □ Available accessories.

ACCESSORIES FOR IVM 40/12-1 H Z22

9.990-266.0




		Order no.	Description	
NOZZLES				
Floor nozzles				
Floor nozzle stainless steel 400 mm DN-F50	43	9.989-935.0		☐
Floor nozzle aluminium 400 mm DN-F40	44	9.989-936.0		☐
Floor nozzle aluminium 400 mm DN-F50	45	9.989-937.0		☐
Aluminium floor nozzle 370 mm DN40	46	9.989-683.0	Floor nozzle, 370 mm, made from aluminium. DN 40.	☐
Aluminium floor nozzle, el, 370 mm, DN40	47	9.989-682.0	Floor nozzle, 370 mm, made from aluminium. Electroconductive. DN 40.	☐
Aluminium floor nozzle 370 mm DN50	48	9.989-664.0	Floor nozzle. 370 mm, made from aluminium. Electroconductive. DN 50.	☐
Aluminium floor nozzle, el, 370 mm, DN50	49	9.987-612.0	Electroconductive multi-purpose floor nozzle. 370 mm wide, DN 50.	☐
Aluminium floor nozzle 500 mm DN50	50	9.989-684.0	Floor nozzle, 500 mm, made from aluminium. Electroconductive. DN 50.	☐
Aluminium floor nozzle, el, 500 mm, DN50	51	9.981-925.0	Floor nozzle with 500 mm suction width and hinge. DN 50, electroconductive.	☐
Stainless steel floor nozzle el 370 mm DN40	52	9.989-558.0	Multi-purpose floor nozzle (370 mm), electroconductive, DN 40.	☐
Stainless steel floor nozzle el 370 mm DN50	53	9.988-115.0	Floor nozzle (370 mm) made from stainless steel, electroconductive, DN 50.	☐
Crevice nozzles				
Crevice nozzle 17 mm × 120 mm DN40	54	9.989-680.0	Electroconductive crevice nozzle, 17 × 120 mm. DN 40.	☐
Crevice nozzle 25 mm × 120 mm DN40	55	9.989-678.0	Electroconductive crevice nozzle, 25 × 120 mm. DN 40.	☐
Crevice nozzle 18 mm × 120 mm DN50	56	9.981-442.0	Electroconductive crevice nozzle made from sheet steel, DN 50, with 17 mm slot width.	☐

☐ Available accessories.

ACCESSORIES FOR IVM 40/12-1 H Z22

9.990-266.0



		Order no.	Description	
NOZZLES				
Crevice nozzles				
Crevice nozzle 25 mm × 120 mm DN50	57	9.981-465.0	Electroconductive crevice nozzle made from sheet steel, DN 50, with 25 mm slot width.	☐
Stainless steel crevice nozzle 17 mm × 120 mm DN40	58	9.989-193.0	Crevice nozzle made from stainless steel, DN 50.	☐
Stainless steel crevice nozzle 22 mm × 220 mm DN50	59	9.988-123.0	Stainless steel crevice nozzle, DN 42, suitable for use with foods.	☐
Flexible crevice nozzles				
Crevice nozzle flexible silicone FDA DN-F50 transparent	60	9.989-847.0		☐
Crevice nozzle flexible silicone FDA DN-F40 transparent	61	9.989-848.0		☐
Flexible crevice nozzle silicone 65 mm DN50	62	9.988-403.0	Flexible crevice nozzle made from silicone, DN 50.	☐
Flexible crevice nozzle 11 mm × 58 mm DN40	63	9.989-681.0	Electroconductive and flexible crevice nozzle, 11 × 58 mm.	☐
Flexible crevice nozzle 20 mm × 45 mm DN40	64	9.981-423.0	Flexible and electroconductive crevice nozzle made from galvanised steel with 20 mm slot width, DN 40.	☐
Flexible crevice nozzle 12 mm × 45 mm DN50	65	9.981-424.0	Flexible, electroconductive galvanised crevice nozzle, DN 50, with 13 mm slot width.	☐
Flexible crevice nozzle 20 mm × 45 mm DN50	66	9.981-425.0	Flexible and electroconductive crevice nozzle made from galvanised steel with 20 mm slot width, DN 50.	☐
Surface nozzles				
Silicone surface nozzle FDA blue DN-F40	67	9.989-849.0		☐
Silicone surface nozzle FDA blue DN-F50	68	9.989-850.0		☐
Silicone surface nozzle FDA green DN-F40	69	9.989-851.0		☐
Silicone surface nozzle FDA green DN-F50	70	9.989-852.0		☐

☐ Available accessories.

ACCESSORIES FOR IVM 40/12-1 H Z22

9.990-266.0



71-72



73-74



75-76



77-78



79-80



81-82



83



84

		Order no.	Description	
NOZZLES				
Surface nozzles				
Silicone surface nozzle FDA red DN-F40	71	9.989-853.0		☐
Silicone surface nozzle FDA red DN-F50	72	9.989-854.0		☐
Silicone surface nozzle FDA transparent DN-F40	73	9.989-855.0		☐
Silicone surface nozzle FDA transparent DN-F50	74	9.989-856.0		☐
Silicone surface nozzle FDA white DN-F40	75	9.989-857.0		☐
Silicone surface nozzle FDA white DN-F50	76	9.989-858.0		☐
Silicone surface nozzle FDA yellow DN-F40	77	9.989-859.0		☐
Silicone surface nozzle FDA yellow DN-F50	78	9.989-860.0		☐
Silicone surface nozzle 120 mm DN40	79	9.988-118.0	Electroconductive rubber nozzle, angled, DN 40, suitable for use with foods.	☐
Silicone surface nozzle 120 mm DN50	80	9.988-119.0	Electroconductive rubber nozzle, angled, DN 50, suitable for use with foods.	☐
Aluminium surface nozzle, 150 mm, DN 40	81	9.989-666.0	Surface nozzle, 150 mm, made from aluminium. DN 40.	☐
Aluminium surface nozzle 150 mm DN50	82	9.989-665.0	Surface nozzle, 150 mm, made from aluminium. DN 50.	☐
BRUSHES				
Standard brushes				
Standard brush 40 mm DN40	83	9.981-431.0	Flat brush nozzle DN 40.	☐
Standard brush 40 mm DN50	84	9.981-432.0	Flat brush nozzle DN 50.	☐

☐ Available accessories.

ACCESSORIES FOR IVM 40/12-1 H Z22
9.990-266.0



		Order no.	Description	
BRUSHES				
End brushes				
Brush FDA blue ø 75 mm DN-F40	85	9.989-873.0		☐
Brush FDA blue ø 75 mm DN-F50	86	9.989-874.0		☐
Brush FDA green ø 75 mm DN-F40	87	9.989-875.0		☐
Brush FDA green ø 75 mm DN-F50	88	9.989-876.0		☐
Brush FDA red ø 75 mm DN-F40	89	9.989-877.0		☐
Brush FDA red ø 75 mm DN-F50	90	9.989-878.0		☐
Brush FDA white ø 75 mm DN-F40	91	9.989-879.0		☐
Brush FDA white ø 75 mm DN-F50	92	9.989-880.0		☐
Brush FDA yellow ø 75 mm DN-F40	93	9.989-881.0		☐
Brush FDA yellow ø 75 mm DN-F50	94	9.989-882.0		☐
End brush Ø 82 mm DN40	95	9.989-609.0	Electroconductive end brush with 82 mm diameter. DN 40.	☐
End brush Ø 82 mm DN50	96	9.989-608.0	Electroconductive end brush with 82 mm diameter. DN 50.	☐
Surface brushes				
Surface brush 300 mm DN40	97	9.981-911.0	Vacuum brush, 300 mm, with 45° connection, with star screw, horsehair bristles.	☐
Surface brush 300 mm DN50	98	9.981-912.0		☐

☐ Available accessories.

ACCESSORIES FOR IVM 40/12-1 H Z22

9.990-266.0



99-102



103, 150-154,
153-154



104-107



108-109, 111-112



110, 113, 152

		Order no.	Description	
BRUSHES				
Cylinder brushes				
Cylinder brush ø 100 mm DN-F40	99	9.989-922.0		☐
Cylinder brush ø 200 mm DN-F40	100	9.989-923.0		☐
Cylinder brush ø 100 mm DN-F50	101	9.989-925.0		☐
Cylinder brush ø 200 mm DN-F50	102	9.989-926.0		☐
HOSES				
PVC				
Hose PVC DN40 1 m	103	9.989-626.0	Electroconductive PVC hose, DN 40. Temperature-resistant up to 85 °C. Length: 1 m.	☐
Hose PVC DN40 3 m	104	9.989-962.0		☐
Hose PVC DN40 5 m	105	9.989-963.0		☐
Hose PVC DN50 3 m	106	9.989-964.0		☐
Hose PVC DN50 5 m	107	9.989-965.0		☐
Hose PVC DN40 3 m	108	9.989-647.0	PVC hose, DN 40. Temperature-resistant up to 85 °C and electrically conductive. Length: 3 m.	☐
Hose PVC DN40 5 m	109	9.989-614.0	Electroconductive PVC hose, DN 40. Temperature-resistant up to 85 °C. Length: 5 m.	☐
PVC hose DN40 15 m without connectors	110	9.989-633.0	PVC hose without tap adapter, DN 40. Electroconductive and temperature-resistant up to 85 °C. Length: 15 m.	☐
Hose PVC DN50 3 m	111	9.989-615.0	Electroconductive PVC hose, DN 50. Temperature-resistant up to 85 °C. Length: 3 m.	☐
Hose PVC DN50 5 m	112	9.989-616.0	Electroconductive PVC hose, DN 50. Temperature-resistant up to 85 °C. Length: 5 m.	☐

☐ Available accessories.

ACCESSORIES FOR IVM 40/12-1 H Z22

9.990-266.0



110, 113, 152



114-115, 117



116



118-119, 121



120, 123



122



124-125



126-127

		Order no.	Description	
HOSES				
PVC				
PVC hose DN50 15 m without connectors	113	9.989-634.0	PVC hose without tap adapter, DN 50. Electroconductive and temperature-resistant up to 85 °C. Length: 15 m.	☐
EVA hoses				
Hose EVA DN40 3 m	114	9.989-982.0		☐
Hose EVA DN40 5 m	115	9.989-983.0		☐
Hose EVA DN50 3 m	116	9.989-984.0		☐
Hose EVA DN50 5 m	117	9.989-985.0		☐
Hose EVA NW40 3 m	118	9.988-088.0	Electroconductive hose with NW 40. Suitable for temperatures up to 65°C. Length: 3 m.	☐
Hose EVA NW40 5 m	119	9.988-089.0	Five-metre-long, electroconductive hose with NW 40. Suitable for temperatures up to 65°C. Length: 5 m.	☐
EVA hose DN40 15 m without connectors	120	9.989-630.0	EVA hose without tap adapter, DN 40. Electroconductive and temperature-resistant up to 65 °C. Length: 15 m.	☐
Hose EVA NW50 3 m	121	9.988-090.0	Electroconductive hose with NW50. Suitable for temperatures up to 65°C. Length: 3 m.	☐
Hose EVA NW50 5 m	122	9.988-091.0		☐
EVA hose DN50 15 m without connectors	123	9.989-631.0	EVA hose without tap adapter, DN 50. Electroconductive and temperature-resistant up to 65 °C. Length: 15 m.	☐
Hose installation sets				
Hose installation kit DN40	124	9.989-627.0	Multipiece hose connection set, DN 40.	☐
Hose installation kit DN50	125	9.989-628.0	Multipiece hose connection kit, DN 50.	☐
Hose connection kit, stainless steel AISI 304 DN40	126	9.989-986.0	Hose connection kit in nominal width DN 40, made of stainless steel. Contents: 1 hose connection piece, 1 hose connection (rotating), 2 hose clamps, 2 hose end pieces (black), 1 flat bag (PE plastic).	☐

☐ Available accessories.

ACCESSORIES FOR IVM 40/12-1 H Z22

9.990-266.0



		Order no.	Description	
HOSES				
Hose installation sets				
Hose connection kit, stainless steel AISI 304 DN50	127	9.989-987.0	Hose connection kit in nominal width DN 50, made of stainless steel. Contents: 1 hose connection piece, 1 hose connection (rotating), 2 hose clamps, 2 hose end pieces (black), 1 flat bag (PE plastic).	☐
PU hoses				
Hose PU DN40 3 m	128	9.989-966.0		☐
Hose PU DN40 5 m	129	9.989-967.0		☐
Hose PU DN50 3 m	130	9.989-968.0		☐
Hose PU DN50 5 m	131	9.989-969.0		☐
Hose PU FDA DN40 3 m	132	9.989-970.0		☐
Hose PU FDA DN40 5 m	133	9.989-971.0		☐
Hose PU FDA DN40 15 m	134	9.989-972.0		☐
Hose PU FDA DN50 3 m	135	9.989-973.0		☐
Hose PU FDA DN50 5 m	136	9.989-974.0		☐
Hose PU FDA DN50 15 m	137	9.989-975.0		☐
Hose PU DN40 3 m	138	9.989-617.0	Oil-resistant, electroconductive PU hose, DN 40. Suitable for abrasive suction media and temperature-resistant up to 80 °C. Length: 3 m.	☐
Hose PU DN40 5 m	139	9.989-618.0	Oil-resistant, electroconductive PU hose, DN 40. Suitable for abrasive suction media and temperature-resistant up to 80 °C. Length: 5 m.	☐
PU hose DN40 15 m without connectors	140	9.989-637.0	PU hose without tap adapter, DN 40. Electroconductive and temperature-resistant up to 80 °C. Length: 15 m.	☐

☐ Available accessories.

ACCESSORIES FOR IVM 40/12-1 H Z22

9.990-266.0



		Order no.	Description	
HOSES				
PU hoses				
Hose PU DN50 3 m	141	9.989-619.0	Oil-resistant, electroconductive PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 80 °C. Length: 3 m.	☐
Hose PU DN50 5 m	142	9.989-620.0	Oil-resistant, electroconductive PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 80 °C. Length: 5 m.	☐
PU hose DN50 15 m without connectors	143	9.989-638.0	PU hose without tap adapter, DN 50. Electroconductive and temperature-resistant up to 80 °C. Length: 15 m.	☐
ME-PU-hoses				
Hose ME DN40 3 m	144	9.989-976.0		☐
Hose ME DN40 5 m	145	9.989-977.0		☐
Hose without connection ME DN40 15 m	146	9.989-978.0		☐
Hose ME DN50 3 m	147	9.989-979.0		☐
Hose ME DN50 5 m	148	9.989-980.0		☐
Hose without connection ME DN50 15 m	149	9.989-981.0		☐
Hose ME-PU DN40 3 m	150	9.989-621.0	Electroconductive, oil-resistant ME-PU hose, DN 40. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 3 m.	☐
ME-PU hose, DN 40, 5 m	151	9.989-622.0	Electroconductive, oil-resistant ME-PU hose, DN 40. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 5 m.	☐
ME-PU hose DN40 15 m without connectors	152	9.989-640.0	Electroconductive, oil-resistant ME-PU hose without tap adapter, DN 40. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 15 m.	☐
Hose ME-PU DN50 3 m	153	9.989-623.0	Electroconductive, oil-resistant ME-PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 3 m.	☐
Hose ME-PU DN50 5 m	154	9.989-625.0	Electroconductive, oil-resistant ME-PU hose, DN 50. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 5 m.	☐

☐ Available accessories.

ACCESSORIES FOR IVM 40/12-1 H Z22


9.990-266.0



		Order no.	Description	
HOSES				
ME-PU-hoses				
ME-PU hose DN50 15 m without connectors	155	9.989-641.0	Electroconductive, oil-resistant ME-PU hose without tap adapter, DN 50. Suitable for abrasive suction media and temperature-resistant up to 110 °C. Length: 15 m.	☐
HANDLES				
Elbow aluminium 45° DN40	156	9.989-544.0	45° curved handle made from aluminium, DN 40.	☐
Elbow aluminium 45° DN50	157	9.989-547.0	Handle with 45° bend. Made from aluminium, DN 50.	☐
Handle stainless steel AISI 304 DN40	158	9.989-896.0		☐
Handle stainless steel AISI 304 DN50	159	9.989-897.0		☐
Handle straight stainless steel AISI 304 DN40	160	9.989-898.0		☐
Handle straight stainless steel AISI 304 DN50	161	9.989-899.0		☐
Handle carbon 45° DN-F40	162	9.989-916.0		☐
Handle carbon 45° DN-F50	163	9.989-917.0		☐
Handle carbon 110° DN-F40	164	9.989-918.0		☐
Handle carbon 110° DN-F50	165	9.989-919.0		☐
Handle DN 40	166	9.977-679.0	45° curved and electroconductive handle made from stainless steel. Inner cone DN 40.	☐
Handle DN50, curved	167	9.977-678.0	Electroconductive and 45° curved handle made from stainless steel. Inner cone DN 50.	☐
Stainless steel handle NW40	168	9.989-036.0	Curved and electroconductive handle made from stainless steel. Angle 45°, inner cone NW 40.	☐

☐ Available accessories.

ACCESSORIES FOR IVM 40/12-1 H Z22
9.990-266.0




		Order no.	Description	
HANDLES				
Stainless steel handle NW50	169	9.988-111.0	Curved and electroconductive handle made from stainless steel. Angle 45°, inner cone NW 50.	☐
SUCTION TUBES				
Carbon suction tube 1500 mm DN40	170	9.989-552.0	Very light carbon extension tube, electroconductive, DN 40. Length: 1500 mm.	☐
Carbon suction tube 1500 mm DN50	171	9.989-553.0	Electroconductive, very light carbon extension tube. Inner cone DN 50, 1500 mm long.	☐
Suction tube stainless steel AISI 304 DN40	172	9.989-912.0		☐
Suction tube stainless steel AISI 304 DN50	173	9.989-913.0		☐
Suction tube carbon 1500 mm DN-F40 conical	174	9.989-920.0		☐
Suction tube carbon 1500 mm DN-F50 conical	175	9.989-921.0		☐
Suction tube aluminium high temperature 1000 mm DN-F40	176	9.989-928.0		☐
Suction tube aluminium high temperature 1000 mm DN-F50	177	9.989-929.0		☐
Suction tube aluminium high temperature 2000 mm DN-F40	178	9.989-930.0		☐
Suction tube aluminium high temperature 2000 mm DN-F50	179	9.989-931.0		☐
Suction tube aluminium high temperature 3000 mm DN-F40	180	9.989-932.0		☐
Suction tube aluminium high temperature 3000 mm DN-F50	181	9.989-933.0		☐
Suction tube 850 mm DN 40	182	9.977-525.0	Steel extension tube, electroconductive, DN 40. Length: 850 mm.	☐

☐ Available accessories.

ACCESSORIES FOR IVM 40/12-1 H Z22


9.990-266.0



182-183



184-185



186-187



188-189



190-191



192-193



194



195

		Order no.	Description	
SUCTION TUBES				
Suction tube 850 mm DN 50	183	9.977-531.0	850 mm long extension tube made from steel. Electroconductive and with inner cone DN 50.	☐
Aluminium suction tube 1500 mm NW40	184	9.989-038.0	Aluminium extension tube, electroconductive, NW 40. Length: 1500 mm.	☐
Aluminium suction tube 1500 mm NW50	185	9.989-035.0	Electrically conductive suction tube (1500 mm) made of aluminium with 50 mm diameter.	☐
Stainless steel suction tube 850 mm NW40	186	9.989-039.0	Stainless steel extension tube, electroconductive, NW 40. Length: 850 mm.	☐
Stainless steel suction tube 850 mm NW50	187	9.988-114.0	Electroconductive extension tube made from stainless steel. Inner cone NW 50.	☐
ADAPTERS / REDUCERS / DISTRIBUTORS				
Accessories adapter				
Adapter Food DN-F50	188	9.993-011.0		☐
Adapter Food DN-F40	189	9.993-012.0		☐
Reducers/expanders				
Reduction DN70 to DN50	190	9.977-772.0		☐
Reduction DN70 to DN40	191	9.989-690.0	Electroconductive steel reducer for reduction from DN 70 to DN 40.	☐
Stainless steel reducer DN 70 to DN 50	192	9.989-712.0		☐
Stainless steel reducer DN 70 to DN 40	193	9.989-713.0		☐
Reduction DN70 to ø 50mm	194	9.977-585.0		☐
PRE-SEPARATORS				
Pre-separator				
Pre-separator Tc Op liquids 125 l DN70	195	9.989-686.0	125 litre pre-separator, DN 70.	☐
Pre-separator Ef solid materials 100 l DN70	196	9.982-238.0	Mobile pre-separator station with 110 l volume and emptying flap.	☐

☐ Available accessories.